

**STYLE****628.25 AS**

<b>Product</b>	<b>PTFE GLASS FABRIC</b>
<b>Product category</b>	<b>BLACK ANTI - STATIC SERIE</b>
<b>Coating</b>	<b>PTFE</b>

<b>Feature</b>	<b>Value</b>	<b>Unit</b>
<b>Nominal thickness</b>	<b>0,230</b>	<b>mm.</b>
<b>Weight</b>	<b>470</b>	<b>gr/m<sup>2</sup></b>
<b>PTFE content</b>	<b>57</b>	<b>%</b>
<b>Tensile strenght</b>	<b>2300</b>	<b>N/5 cm.</b>
<b>Max. operating temperature continuous</b>	<b>260</b>	<b>°C</b>

Note:Nominal thickness, tensile strenght and PTFE content values are typical and are not intended as a specification minimum.  
Weight Tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained here in are based on test results FIBERFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.

**F I B E R F L O N**

CORLU - CERKEZKOY ROAD 7. KM.  
59860 CORLU – TEKIRDAG  
TURKEY

TEL : +90 282 676 42 08 (pbx)  
FAX : +90 282 676 41 98

[www.fiberflon.com](http://www.fiberflon.com)  
[info@fiberflon.com](mailto:info@fiberflon.com)