

# 216.15 AS



Product	Product category	Coating
PTFE GLASS FABRIC	BLACK ANTI-STATIC SERIE	PTFE

Properties	Metric		Imperial	
Standard width(s) <i>Please ask for other widths</i>	1000	mm	39.5	inches
Thickness	0,14	mm	0.0055	inches
Weight	296	gr/m <sup>2</sup>	8.73	oz/sq yd
PTFE content	63	%	63	%
Surface resistance	< 100	kohm/sq	< 100	kohm/sq
Tensile strength	1200	N/5 cm	137	Ibs/inches
Temperature resistance	-150 to 260	°C	-238 to 500	°F

Anti-static products are made with a specially formulated black PTFE coating. These fabrics eliminates static electricity during operation. Conductive black products are widely used in the apparel industry as conveyor belts in fusing press machines. The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m<sup>2</sup> = ±%5  
 All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results FIBERFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.  
 All data is subject to change without notice.