

FIBERTEX 500



Product	Product category	Coating
PTFE GLASS FABRIC FLEXIBLE COMPOSITE	FIBERTEX SERIE	PTFE

Properties	Metric		Imperial	
Standart width(s) <i>Please ask for other widths</i>	1500	mm	59.1	inches
Thickness	0,35	mm	0.0138	inches
Weight	700	gr/m ²	20.65	oz/sq yd
PTFE content	60	%	60	%
Tensile strength	3500	N/5 cm	400	Ibs/inches
Tear resistance (<i>Trapez</i>)	400	N	90	Ibs
Temperature resistance	310	°C	590	°F

Fibertex fabric expansion joint composites:

High quality woven fiberglass fabrics coated with a specially formulated fluoropolymer coating designed to provide enhanced flex properties and excellent high temperature performance, fire and chemical resistance, release, and weatherability properties for non-metallic expansion joints.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5
 All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained here in are based on test results FIBERFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.
 All data is subject to change without notice.