

SIL 025 W



Product	Product category	Coating
SILICONE RUBBER COATED GLASS FABRIC	SILICONE BOTH SIDE	SILICONE RUBBER

Properties	Metric		Imperial	
Standart width(s) <i>Please ask for other widths</i>	1000	mm	39.5	inches
Thickness	0,28	mm	0.0110	inches
Weight	400	gr/m ²	11.80	oz/sq yd
Temperature resistance	-70 to 230	°C	-158 to 446	°F

Glass fabrics coated on both side with silicone rubber.

- Hi-temperature resistant
- Excellent release properties
- Superior abrasion resistance
- Good chemical resistance
- Superior dielectric properties

Fiberflon silicone coated fabrics can be used a wide range of industrial applications, such as; Shrink tunels, foam manufacturing, electrical insulation tapes, conveyor belts, fabric expansion joints, safety curtains, release and separator sheets, gasketing.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



Note: Nominal thickness and weight values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5
 All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained here in are based on test results FIBERFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.
 All data is subject to change without notice.