

# SIL-AD



Product	Product category	Coating
SILICONE GLASS SELF ADHESIVE TAPE	ADHESIVE TAPE SERIE	SILICONE PSA

Properties	Metric		Imperial	
Total thickness	0,26	mm	0.0102	inches
Adhesion	20	N/5 cm	37	oz/inches
Temperature resistance	230	°C	446	°F
Colour	Red		Red	
Core ID	Ø 76	mm	Ø 3	inches

**HI-FRICTION ROLL COVERING TAPE FOR TEXTILE DRYERS**

SIL-AD Tape will provide hi-friction surface on drive roller and will prevent teflon coated open-mesh belt from sliding. If metal drive roller is covered by SIL-AD Tape, operators do not need to increase belt tension. This will improve the belt's life.

SIL-AD Tape has a high temperature resisting adhesive on back (covered with yellow liner) which makes it very easy to cover the roller. Metal roller surface should be free off dust, oil etc. (if necessary, it should be cleaned with xylene or acetone). Liner can easily be take off from tape and covered on to the roller.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



Note: Nominal thickness, tensile strength and adhesion values are typical and are not intended as a specification minimum. All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained here in are based on test results FIBERFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed. All data is subject to change without notice.